

## DECLARATION OF PERFORMANCE

Declaration No. HS/DP/EP02/CPR31052013

1. Unique identification code of the product type:

**BS EN 1341 – Slabs of natural stone for external paving.**

2. Type, batch, serial number or any other element allowing identification of the construction product as required under Article 11(4):

**Kandla Grey.Poddar Udyog, 125 Dashera Scheme, Kota – 324009 (Rajasthan) INDIA**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:

**External Paving.**

4. Name, registered trade name or registered trademark and contact address of manufacturer as required under Article 11(5):

**Poddar Udyog, 125 Dashera Scheme, Kota – 324009 (Rajasthan) INDIA.**

5. Where applicable name and contact address of the authorised representative whose mandate covers the tasks specified in article 12(2).

**Jabbir Ahmed. Khotah Stone Ltd. Two Acres. Preston New Rd. Samlesbury. Preston. Lancashire. PR5 0UL**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V.

**Attestation System 4**

7. In the case of the declaration of performance covering a construction product covered by a harmonised Standard.

**The Manufacturer has carried out the initial assessment and continuous surveillance of the factory production control system and its requirements.**

8.Declared performance

| Essential characteristics               | Performance                        | Harmonised technical specification |
|---|------------------------------------|------------------------------------|
| Water Absorption % by Weight            | 0.42                               | EN-13755:2001                      |
| Chemical Resistance                     | Pass                               | EN-1341:2001                       |
| Compressive Strength kg/cm <sup>2</sup> | 565.40                             | EN-1926:1999                       |
| Flexural Strength, MPa                  | 34.80                              | EN-12372:2006                      |
| Frost Resistance MPa                    | 12 cycles 33.20<br>48 cycles 32.80 | EN-12372:2006<br>EN-12371:2001     |
| Resistance to wear                      | 6.20mm (Mean)<br>6.60mm (LEV)      | EN-14157;2004                      |
| Slip Resistance                         | SRV Dry 74<br>SRV Wet 60           | EN-14231:2003                      |
| Flatness (mm)                           | 0.60                               | EN-1341:2012                       |
|   |                                    |                                    |
|   |                                    |                                    |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Jabbir Ahmed

.....

(MD)

Preston, Lancashire 31.05.13

.....  
(place and date of issue)

  
(signature)