

## DECLARATION OF PERFORMANCE

(Declaration Number) HS/DP/MU04/CPR31052013

1. Unique Identification code of the product type.

### **BS EN 771-6:2011 Natural Stone Masonry Units**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4) of the CPR.

### **Red/Pink Mix Random Walling. Containing a mix of any of the following Stone Types;**

**St. Bees Sandstone.** Grange Quarry. Parkhouse Yard. Bigrigg. Egremont. Cumbria. CA22 2TL

**Corsehill Sandstone** Eaglesfield Rd. Annan. Dumfries & Galloway.

**Cove Sandstone** Brownknowe, Kirtlebridge, Dumfries & Galloway.

**Corncockle Sandstone** Templand, Lochmaben, Lockerbie. Dumfries & Galloway.

**Doddington Sandstone** Doddington, Nr Wooler. Northumberland NE71 6AN

**Dukes Gritstone** Robin Lane, Whatstandwell, Derbyshire.

**Wattscliff Lilac Sandstone** Cliffe Lane, Elton. Derbyshire.

**Brownieside Sandstone** Brownieside, South Charlton. Northumberland

3. Intended use of the construction product.

### **Squared Rubble Stone, Rubble Stone**

4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5).

### **Hutton Stone Co Ltd. West Fishwick. Berwick upon Tweed. Scottish Borders TD15 1XQ**

5. Where applicable name and contact address of the authorised representative whose mandate covers the tasks specified in article 12(2).

### **Not Applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V.

### **Attestation System 4**

7. In the case of the declaration of performance covering a construction product covered by a harmonised Standard.

### **The Manufacturer has carried out the initial assessment and continuous surveillance of the factory production control system and its requirements.**

8. Declared performance


Essential characteristics	Performance	Harmonised technical specification
Resistance to fire	Class A 1	Without Testing (see decision 96/603/EC, as amended)
Shear Bond Strength	Fixed Value	BE-EN 998-2 2010, Annex C
Apparent Density	NPD	BS EN 1936 BS EN 1936
Open Porosity	NPD	
Water Absorption Coefficient by Capillarity	NPD	BS EN 772-11
Compressive Strength	NPD	BS EN 772-1
Flexural Strength (3 Point) Orientation Perpendicular	NPD	BS EN 12372
Frost Resistance Identification. Max 168 Cycles	NPD	BS EN 12371
Thermal Conductivity	NPD	BS EN 1745

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

M. Paine. MANAGING DIRECTOR.  
 (name and function)

WEST FISHWICK 31.05.13  
 (place and date of issue)

  
 (signature)